

ATK

Single Circuit Extruded Aluminum Track, 2-12 Feet Track & Power Feeds



Job Information

Project Name	
Type	
Location	
Quantity	
Date	

Description

The ATK series is an extruded aluminum track for use with A-Line track fixtures. Available in 2', 4', 6', 8' and 12' nominal length.

Features

Extrusion

Constructed of 0.06" extruded aluminum with 0.045" PVC bus bar support holding 12 gauge round bus bars. Polarity groove is located on face of track to indicate location of grounding conductor.

Mounting

This track is surface mounted using the supplied mounting hardware. Suspended mounting is available with accessories (ordered separately).

Labels

cULus listed.

Electrical

Single circuit power distribution system designed to supply lighting unit flexibly. Single hot and neutral conductors are rated for maximum capacity of 20 Amps (2400 watts per circuit) at 120V. Copper electrical conductors are concealed in thermo-plastic, low-profile track section.

Compatibility

Track system is compatible with all A-Line® and Juno® style track fixtures, accessories and connectors.

Technical Drawings



Part No.	Length (Excluding end caps)
ATK02	20 1/8" (511mm)
ATK04	44 1/8" (1121mm)
ATK06	68 1/8" (1730mm)
ATK08	92 1/8" (2340mm)
ATK12'	140 1/8" (3559mm)



SPECIFICATION

Warranty	5 Years
----------	---------

Ordering Guide

Length	Colour
ATK	
02 : 2'	BK : Black
04 : 4'	BN : Brushed Nickel
06 : 6'	SL : Silver
08 : 8'	WH : White
12 : 12'	

Example: ATK04-BN

Notes:

¹ The 12-foot option is not available in the US. We recommend using an 8-foot section along with a 4-foot section and a joiner to achieve your desired 12-foot run. Accessories should be ordered separately. For additional options please consult your A-Line Lighting representative. Juno is a registered trademark of Juno Lighting Group. Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Accessories

	ATK02-PDW 2' Precision Pro Channel, 1/2" drywall, for single circuit track.		ATKA310 A-Line track pendant adapter, chain.		A-BEAM-10AC-xx 10' Aircraft cable set with canopy.
	RODF Hollow suspension rod kit used to suspend track lighting from track.		ATKA31A A-Line track pendant adapter, cord.		A-BEAM-20AC-xx 20' Aircraft cable set with canopy.
	RODR 12" Hollow stem rod used to suspend track from ceiling.		ATKA321 A-Line track receptacle, accepts 3-prong plugs.		A-BEAM-310PF-xx 12 / 3 SJT 10' cord with canopy.
	ATKXW Track suspension rod system		ATKA320 A-Line track hook. 7lb maximum weight.		A-BEAM-320PF-xx 12 / 3 SJT 20' cord with canopy.
	A-TDR62 Hollow stem rod kit used to suspend rack system from ceiling.		ATKM420 Track suspension kit for A-Line track systems, 180" aircraft cable.		ATKM421 A-Line Universal Track Suspension Kit, 250" AC
	ATKA250 4.75" Sloped Ceiling Canopy Kit. For use with track down-rods 2"-96".				

Connectors & Power Feeds

	ATKC01 Single circuit 'I' connector.		ATKP02 Single circuit 'L' and 'I' power feed connector.		ATKP03 Single circuit 'T' power feed connector.
	ATKC05 Single circuit flexible connector.		ATKP06 Single circuit live end conduit feed.		ATKP06R Single circuit live end conduit feed, reverse.
	ATKP09 Single circuit live end power feed.		ATKP10 Single circuit wired end power feed, with 15' plug-in cord.		ATKP109 Single circuit monopoint power feed.
	ATKP04-1C Single circuit 'X' power feed connector.		ATKP08 Single circuit center feed.		ATKP11 Single circuit live end power feed with canopy cover.

Compatible LED Track Fixtures

	APOLLO LED		ATF7425		Flight (ATF7607)
	ATF7250		ATF7509		Flight (ATF7610)
	ATF7415		ATF7545		ATF7630
	SORA LED		TEARDROP		DINE (T-LEDDNG)
	ATLAS		DELTA		FLEX
	FOCUS (ATF8010)				

Current Limiters

	ATKPCL-06-1C Single circuit live end narrow current limiter, 1-14 amp options		ATKPCL-09-1C Single circuit dual live end canopy current limiter, 1-14 amp options		ATKPCL-11-1C Single circuit live end canopy current limiter, 1-14 amp options
--	---	--	--	--	---